



## TECHNICAL DATASHEET CLEANING HIGH PRESSURE LAMINATE (HPL) AND SOLID GRADE LAMINATE (SGL)

This care guideline applies to all vertical and horizontal sheet materials for HPL and SGL.

BioCarbon Liscio Laminates have separate care guidelines.

Our surface sheet materials are supplied with an Anti-Bacterial and Anti-Microbial protection as standard, which contains silver ions. This surface protection contributes to the general hygiene management by increasing surface hygiene via reduction of spread of microorganisms.

Please note, with all spillages it is important to clean them as quickly as possible using the guidelines below, particularly with high colourant liquids i.e. cranberry juice, and certain types of bleach to prevent staining to the surface.

It is recommended when using cleaning products to follow direction for use of the cleaning product manufacturer. Always test cleaning products for suitability on an inconspicuous area before further application. Do not use abrasive cleaning solutions or sponges as they will damage the surface texture.

	CONTAMINANT	EXAMPLES	RECOMMENDATION
BASIC CLEANING	Light liquids	Milk, tea, coffee, cordial, fruit juices	Wipe with a soft cloth and cold water.
	Heavy / coloured liquids	Fats, thick sauces, wine	Wipe with a soft cloth, warm water and washing up liquid or a degreasing multi-purpose cleaner. Rinse and dry with a soft cloth.
	Sticky substances	Chewing gum, water-based paints	Wipe with a soft cloth, hot water and washing up liquid or a degreasing multi-purpose cleaner. Rinse and dry with a soft cloth. If the stain is dry use acetone and a soft cloth.
DEEP CLEANING	Polishes	Polish, nail polish, oils	Wipe with an acetone and a soft cloth.
	Adhesives and solvent-based paints	Adhesives, synthetic oil paints	Use a solvent such as ethanol and wipe with a soft cloth.
SPECIAL CARE CLEANING	Spray paints	Spray paints, graffiti and very sticky adhesives	Wipe with a nitromethane solution, only cleaning the surface for a short timeframe and rinse with water and a soft cloth.
	Limescale	Limescale	Mix a washing up liquid with 10% citric acid solution and rinse with hot water and a soft cloth.
	Silicone	Silicone, paraffin, and wax	To prevent scratching remove carefully with a plastic or wooden spatula, but only if substance is wet. If the substance has dried this might not be possible to remove.

### MORE INFO

For more information please contact our UK Distributor Performance Panels Ltd:

- ☎ +44 (0) 1422 310319
- ✉ info@performance-panels.co.uk
- 🌐 www.performance-panels.co.uk