



PROBAND FIX



DESCRIPTION

PROBAND FIX is a moisture-cure sealant with high adhesion and elasticity, available in white and grey colour. It is suitable for the installation of **PROBAND 150 / 250** onto non-absorbent wall surfaces such as PVC, wood, polycarbonate, glass, plastic and metal. It can be also used, using **PROBAND 150 / 250**, to waterproof the junction between two adjacent rolls of **PROFOIL** in swimming pools and water tanks and to seal the joint between tiles and edging profiles of the **PROTERRACE** line.

PROBAND FIX is a stable compound and guarantees the sealing of absorbent materials such as marble and natural stone.

PRODUCT PLUS

- High elasticity
- UV resistant
- High chemical stability
- Suitable for natural stones
- It is not a special waste

AREAS OF USE

Use

Inside and outside environments as balconies, terraces, bathrooms, kitchens and saunas. **PROBAND FIX** allows the **PROBAND 150 / 250** installation onto PVC, wood, polycarbonate, glass, plastic, metal and non-absorbent supports. Using **PROBAND 150 / 250** and

PROBAND FIX it is suitable to waterproof two adjacent rolls of **PROFOIL** in swimming pool and water tanks and to seal the joint between tiles and edging metal profiles of the **PROTERRACE** line.

Do not use

On bituminous coverings, to waterproof walkable surfaces and lightweight screeds and in contact with adhesive containing solvents.

INSTALLATION INSTRUCTIONS

Perimeter joints

1. Apply **PROBAND FIX** on the non-absorbent wall using a 2 mm notched trowel.
2. Apply the cement adhesive on the membrane filling the cavities.
3. Place **PROBAND 150 / 250** following the wall-floor joint; press and smooth **PROBAND 150 / 250** preventing creases.

Joint between adjacent PROFOIL rolls

1. Apply **PROBAND FIX**, using a 2 mm notched trowel, along the joints between two adjacent rolls of **PROFOIL** to a width slightly less than the **PROBAND 150 / 250**.
2. Place **PROBAND 150 / 250** onto the sealant following the joint between the sheets; press and smooth **PROBAND 150 / 250** preventing creases.

CLEANING OF THE TOOLS

Any remains of **PROBAND FIX** can be removed using diluent or alcohol while the product is still wet.

TEXT TEMPLATE FOR TENDERS

Supply and installation of grey / white moisture-cure sealant with high adhesion and elasticity, suitable for the installation of **PROBAND 150 / 250** onto non-absorbent wall surfaces such as PVC, wood, polycarbonate, glass, plastic and metal / to waterproof, using **PROBAND 150 / 250**, the junction between two adjacent rolls of **PROFOIL** in swimming pools and water tanks / to seal the joint between tiles and edging profiles of the **PROTERRACE** line, like **PROBAND FIX** of the Progress Profiles company.

PRBFXB/G : Single-component moisture-cure sealant.

Quantity: _____ pz
Material: _____ €/pz
Application: _____ €/mt
Total value: _____ €/mt



PROBAND FIX

TECHNICAL DATA

Appearance	White or grey thixotropic paste	
Specific weight of the mixture	≈ 1,65 Kg / dm ³	
Shelf life	18 months in the original package in a dry and cool environment	
Cartridge	290 ml	
Consumption for sealing Profoil with Proband 150	1 cartridge 4 ml	
Maximum allowed movement	≤ 10 %	ISO 9046
Temperature range of application	+ 5 °C / + 40 °C	
Skinning	≈ 10 min	
Curing	≈ 2 mm / 24 h	
Interval before normal use	≈ 7 days	

Data collected at + 023°C, 50% relative humidity and without ventilation.

PERFORMANCE HIGT – TECH

Shore A hardness	75	DIN 53 505
Modulus of elasticity	≈ 0,5 N / mm ²	ISO 8339
Ultimate elongation	300 %	
Working temperature	- 40 °C / + 100 °C	
Resistance to atmospheric agents	excellent	
Resistance to ageing	good	
U.V. resistance	good	

Data collected at +23°C, 50% relative humidity, without ventilation