



## INTERLACED BOW TOP RAILINGS

INTERLACED BOW TOP RAILING IS AN ATTRACTIVE ALTERNATIVE TO STANDARD BOW TOP AS IT FEATURES A DECORATIVE INTERLOCKING PATTERN THAT IS BOTH AESTHETICALLY PLEASING WHILE ADDING FURTHER SECURITY AND PROTECTION. ITS LACK OF SHARP EDGES MAKES IT AN IDEAL CHOICE FOR USE IN PUBLIC PARKS, TRADITIONALLY AS A BOUNDARY TO PLANTED AREAS OR ALONGSIDE FOOTPATHS.



### SUITABLE FOR

- RETAIL
- SCHOOLS
- PARKS
- PLAY AREAS
- PUBLIC SPACES
- HOUSING DEVELOPMENTS

### TECHNICAL INFORMATION

- MANUFACTURED IN ACCORDANCE TO BS 1722-9
- HOT DIP GALVANIZED TO BS EN 1461
- POWDER COATED OPTION TO ANY RAL OR BS COLOUR
- PANEL TO POSTS FIXINGS INCLUDED
- MATERIAL - SOLID SECTIONS S275JR
- FIXING METHODS: GROUND FIXED INTO CONCRETE FOUNDATIONS, BASE PLATED FIXING, ROOTED INTO POCKETS
- SINGLE AND DOUBLE LEAF GATES AVAILABLE TO SUIT

|              |  |
|--------------|--|
| Post Centres | 2000mm max                                   |
| Panel Height | 500mm, 900mm, 1200mm, Bespoke                |
| Frame Size   | 40x10 RSF, 60x10 RSF                         |
| Bow Size     | 12mm (upto 1.2m high), 16mm (upto 1.4m high) |