

Test Report

SPONSOR: **Mayne Inc.**
Langley, British Columbia, Canada

Sound Absorption
RAL™-A19-487

CONDUCTED: 2019-12-02

Page 1 of 9

ON: Linear Metal Ceilings: Link & Lock Beams (6 in. Link & Lock Beams) with fiberglass backer

TEST METHODOLOGY

Riverbank Acoustical Laboratories™ is accredited by the U.S. Department of Commerce, National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP) as an ISO 17025:2017 Laboratory (NVLAP Lab Code: 100227-0) and for this test procedure. The test reported in this document conformed explicitly with ASTM C423-17: "Standard Test Method for Sound Absorption and Sound Absorption Coefficients by the Reverberation Room Method." The specimen mounting was performed according to ASTM E795-16: "Standard Practices for Mounting Test Specimens During Sound Absorption Tests." A description of the measurement procedure and room specifications are available upon request. The results presented in this report apply to the sample as received from the test sponsor.

INFORMATION PROVIDED BY SPONSOR

The test specimen was designated by the sponsor as Linear Metal Ceilings: Link & Lock Beams (6 in. Link & Lock Beams) with fiberglass backer. The following nominal product information was provided by the sponsor prior to testing. The accuracy of such sponsor-provided information can affect the validity of the test results.

Product Under Test

Trade Name: Linear Metal Ceilings: Link & Lock Beams
Depth: 152.4 mm (6 in.)
Backer Density: 48.1 kg/m³ (3 lbs/ft³)
Manufacturer: Longboard Products

SPECIMEN MEASUREMENTS & TEST CONDITIONS

Through a full external visual inspection performed on the test specimen, Riverbank personnel verified the following information:

Test Specimen

Materials: Hollow metal beams over rigid fiberglass backer
Dimensions: Beams, 18 @ 2438.4 mm (96 in.) long x 152.4 mm (6 in.) wide
x 41 mm (1.614 in.) thick
Fiberglass backer @ 2743.2 mm (108 in.) x 2438.4 mm (96 in.)
Thickness: Beam wall @ 1.8 mm (0.071 in.)
Fiberglass backer @ 25.4 mm (1 in.)

Test Report

Mayne Inc.
2019-12-02

RAL™-A19-487
Page 2 of 9

Test Specimen (continued)

Overall Weight: Beams @ 102.85 kg (226.75 lbs)
 Fiberglass backer @ 7.94 kg (17.5 lbs)
Density: Fiberglass backer 46.7 kg/m³ @ (2.92 lbs/ft³)

Physical Measurements (per beam)

Dimensions: 0.15 m (6.0 in) wide by 2.44 m (96.0 in) long
Thickness: 41 mm (1.614 in.)
Weight: 5.72 kg (12.6 lbs)

Test Environment

Room Volume: 291.98 m³
Temperature: 21.4 °C ± 0.2 °C (Requirement: ≥ 10 °C and ≤ 5 °C change)
Relative Humidity: 54.4 % ± 1.2 % (Requirement: ≥ 40 % and ≤ 5 % change)
Barometric Pressure: 98.9 kPa (Requirement not defined)

Each sound absorbing unit had an absorptive area (all exposed surfaces) of 0.94 m² (10.13 ft²). The total absorptive area (all exposed surfaces) of all sound-absorbing units was 16.93 m² (182.25 ft²). The array of units covered 6.51 m² (70.08 ft²) of the horizontal test surface (total treated area).

MOUNTING METHOD

Type J Mounting: The specimen is an array of 18 spaced rectangular baffles laid on the horizontal test surface over the fiberglass backer, such that their width is oriented vertically. The baffles were spaced 152.4 mm (6 in.) on center.

Test Report

Mayne Inc.
2019-12-02

RAL™-A19-487
Page 3 of 9




Figure 1 – Specimen mounted in test chamber



Figure 2 – Cross section of individual beam

1512 S BATAVIA AVENUE
 GENEVA, IL 60134
 630-232-0104

An **ALION** Technical Center

RIVERBANK.ALIONSCIENCE.COM

FOUNDED 1918 BY
 WALLACE CLEMENT SABINE

Test Report

Mayne Inc.
 2019-12-02

RAL™-A19-487
 Page 4 of 9

TEST RESULTS


Note: There is currently no standardized method for calculating Absorption Coefficients from spaced object absorbers. The sound absorption performance of spaced object absorbers should not be compared directly with specimens tested as a single rectangular area (e.g. mounting types A, E, etc.).

For the purposes of this report, a single “unit” consists of a single beam and the portion of the fiberglass backer beneath that beam.

1/3 Octave Center Frequency (Hz)	Total Absorption		Absorption per Unit	
	(m ²)	(Sabins)	(m ² / Unit)	(Sabins / Unit)
100	0.83	8.92	0.05	0.50
** 125	2.13	22.90	0.12	1.27
160	1.32	14.17	0.07	0.79
200	2.37	25.55	0.13	1.42
** 250	3.31	35.66	0.18	1.98
315	4.67	50.22	0.26	2.79
400	5.69	61.22	0.32	3.40
** 500	6.00	64.56	0.33	3.59
630	5.68	61.16	0.32	3.40
800	5.63	60.61	0.31	3.37
** 1000	6.16	66.34	0.34	3.69
1250	7.00	75.39	0.39	4.19
1600	6.49	69.91	0.36	3.88
** 2000	6.69	72.06	0.37	4.00
2500	6.53	70.27	0.36	3.90
3150	6.10	65.64	0.34	3.65
** 4000	6.23	67.06	0.35	3.73
5000	5.91	63.56	0.33	3.53

Tested by 
 Marc Sciaky
 Senior Experimentalist

Report by 
 Malcolm Kelly
 Test Engineer, Acoustician

Approved by 
 Eric P. Wolfram
 Laboratory Manager



RIVERBANK ACOUSTICAL LABORATORIES IS ACCREDITED BY NVLAP (LAB CODE 100227-0) FOR ACOUSTICAL TESTING SERVICES IN ACCORDANCE WITH ISO/IEC 17025:2017 AND FOR THIS PROCEDURE. THIS REPORT MUST NOT BE USED BY THE CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY RAL, NVLAP, NIST, OR ANY AGENCY OF THE U.S. GOVERNMENT. THIS REPORT SHALL NOT BE MODIFIED WITHOUT THE WRITTEN APPROVAL OF RAL. THE RESULTS REPORTED APPLY ONLY TO THE SPECIFIC SAMPLE SUBMITTED FOR TESTING; RAL ASSUMES NO RESPONSIBILITY FOR THE PERFORMANCE OF ANY OTHER SAMPLE.

Test Report


Mayne Inc.
2019-12-02

RAL™-A19-487

Page 5 of 9

SOUND ABSORPTION REPORT

Linear Metal Ceilings: Link & Lock Beams (6 in. Link & Lock Beams) with fiberglass backer



Test Report

Mayne Inc.
2019-12-02

RAL™-A19-487

Page 6 of 9

APPENDIX A: Extended Frequency Range Data

Specimen: Linear Metal Ceilings: Link & Lock Beams (6 in. Link & Lock Beams) with fiberglass backer
(See Full Report)

The following non-accredited data were obtained in accordance with ASTM C423-17, but extend beyond the defined frequency range of 100Hz to 5,000Hz. These unofficial results are representative of the RAL test environment only and intended for research & comparison purposes.

1/3 Octave Band Center Frequency (Hz)	Total Absorption		Absorption per Unit	
	(m ²)	(Sabins)	(m ² / Unit)	(Sabins / Unit)
31.5	-1.49	-15.99	-0.08	-0.89
40	-0.84	-9.02	-0.05	-0.50
50	-1.10	-11.86	-0.06	-0.66
63	0.38	4.09	0.02	0.23
80	0.85	9.11	0.05	0.51
100	0.83	8.92	0.05	0.50
125	2.13	22.90	0.12	1.27
160	1.32	14.17	0.07	0.79
200	2.37	25.55	0.13	1.42
250	3.31	35.66	0.18	1.98
315	4.67	50.22	0.26	2.79
400	5.69	61.22	0.32	3.40
500	6.00	64.56	0.33	3.59
630	5.68	61.16	0.32	3.40
800	5.63	60.61	0.31	3.37
1000	6.16	66.34	0.34	3.69
1250	7.00	75.39	0.39	4.19
1600	6.49	69.91	0.36	3.88
2000	6.69	72.06	0.37	4.00
2500	6.53	70.27	0.36	3.90
3150	6.10	65.64	0.34	3.65
4000	6.23	67.06	0.35	3.73
5000	5.91	63.56	0.33	3.53
6300	5.75	61.93	0.32	3.44
8000	6.05	65.16	0.34	3.62
10000	6.23	67.09	0.35	3.73
12500	6.90	74.31	0.38	4.13



NVLAP LAB CODE 100227-0

RIVERBANK ACOUSTICAL LABORATORIES IS ACCREDITED BY NVLAP (LAB CODE 100227-0) FOR ACOUSTICAL TESTING SERVICES IN ACCORDANCE WITH ISO/IEC 17025:2017 AND FOR THIS PROCEDURE. THIS REPORT MUST NOT BE USED BY THE CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY RAL, NVLAP, NIST, OR ANY AGENCY OF THE U.S. GOVERNMENT.

THIS REPORT SHALL NOT BE MODIFIED WITHOUT THE WRITTEN APPROVAL OF RAL. THE RESULTS REPORTED APPLY ONLY TO THE SPECIFIC SAMPLE SUBMITTED FOR TESTING; RAL ASSUMES NO RESPONSIBILITY FOR THE PERFORMANCE OF ANY OTHER SAMPLE.

1512 S BATAVIA AVENUE
GENEVA, IL 60134
630-232-0104

An ALION Technical Center

RIVERBANK.ALIONSCIENCE.COM

FOUNDED 1918 BY
WALLACE CLEMENT SABINE

Test Report

Mayne Inc.
2019-12-02

RAL™-A19-487
Page 7 of 9

APPENDIX B: Instruments of Traceability

Specimen: Linear Metal Ceilings: Link & Lock Beams (6 in. Link & Lock Beams) with fiberglass backer
(See Full Report)

<u>Description</u>	<u>Model</u>	<u>Serial Number</u>	<u>Date of Certification</u>	<u>Calibration Due</u>
System 1	Type 3160-A-042	106968	2019-06-25	2020-06-25
Bruel & Kjaer Mic And Preamp A	Type 4943-B-001	2311428	2019-09-27	2020-09-27
Bruel & Kjaer Pistonphone	Type 4228	2781248	2019-08-09	2020-08-09
Omega Digital Temp., Humid. And Pressure Recorder	OM-CP-PRHTemp2000	P97844	2019-02-08	2020-02-08

APPENDIX C: Revisions to Original Test Report

Specimen: Linear Metal Ceilings: Link & Lock Beams (6 in. Link & Lock Beams) with fiberglass backer
(See Full Report)

<u>Date</u>	<u>Revision</u>
2019-12-16	Original report issued

END

SPONSOR: **Mayne Inc.**
Langley, British Columbia, Canada

Report Referenced: **RAL™-A19-487**
Page 1 of 2

CONDUCTED: 2019-12-02

ON: Linear Metal Ceilings: Link & Lock Beams (6 in. Link & Lock Beams) with fiberglass backer (See Full Test Report for Details)

Appendix D to ASTM C423 Sound Absorption Test

Non-standard calculation of equivalent NRC Rating and Absorption Coefficients from spaced absorbers

At this time ASTM C423 does not provide a standard method for determining absorption coefficients of spaced object absorbers. Tests of a set of sound absorbing objects spaced apart from each other will yield higher absorption rates than a specimen joined together as a single patch (A-Mount or E-Mount). For this reason it is unfair to provide NRC or absorption coefficient ratings for specimens that consist of a spaced set of absorbers. Despite this, the architectural industry has expressed great demand for a simple "single number" rating for these treatments. Likewise, acoustical consultants desire equivalent absorption coefficient data for use in acoustical modeling software. The following is an attempt to appease these demands until ASTM develops a standard method for calculation.

Apparent Sound Absorption Coefficient calculated from total test surface area covered

The total sound absorption yielded by the specimen is divided by the total surface area of the test surface covered by the suspended baffles, including intermediate spaces. The baffle rigging covered 6.51 m² (70.08 ft²) of horizontal test surface area. With an extra 114.3 mm (4.5 in.) of width to account for the space between the tested array and what would be the next baffle in a larger array, the surface area comes to 6.79 m² (73.08 ft²). Apparent Noise Reduction Coefficient (NRC) rating and Sound Absorption Average (SAA) figures are calculated from this data based on the methods described in ASTM C423-17. This may be the most accurate method for comparing baffle arrays to ceiling tile products. The apparent sound absorption coefficient data can be assigned to a single horizontal surface or plane in acoustical modeling software for approximation of baffle array performance. Such approximations rely on the assumptions that baffle spacing is similar to that of the tested array, that the spacing between adjacent rows of baffles is negligibly small, and that the installation occurs over a fiberglass backer similar to that used in the test specimen.

SPONSOR: **Mayne Inc.**
CONDUCTED: 2019-12-02

Report Referenced: **RAL™-A19-487**

Page 2 of 2

Appendix D: Data Note: See full test report for details of mounting position, spacing, and configuration, as these parameters greatly affect sound absorption performance.

Specimen Absorption			Method 1
Freq. (Hz)	Sabins	Sabins / Unit	Apparent Abs. Coefficient From Total Coverage Area
31.5	-15.99	-0.89	-0.22
40	-9.02	-0.50	-0.12
50	-11.86	-0.66	-0.16
63	4.09	0.23	0.06
80	9.11	0.51	0.12
100	8.92	0.50	0.12
125	22.90	1.27	0.31
160	14.17	0.79	0.19
200	25.55	1.42	0.35
250	35.66	1.98	0.49
315	50.22	2.79	0.69
400	61.22	3.40	0.84
500	64.56	3.59	0.88
630	61.16	3.40	0.84
800	60.61	3.37	0.83
1,000	66.34	3.69	0.91
1,250	75.39	4.19	1.03
1,600	69.91	3.88	0.96
2,000	72.06	4.00	0.99
2,500	70.27	3.90	0.96
3,150	65.64	3.65	0.90
4,000	67.06	3.73	0.92
5,000	63.56	3.53	0.87
6,300	61.93	3.44	0.85
8,000	65.16	3.62	0.89
10,000	67.09	3.73	0.92
12,500	74.31	4.13	1.02
			Apparent NRC: 0.80
			Apparent SAA: 0.81

Prepared by 
Malcolm Kelly
Test Engineer, Acoustician