

# Technical data sheet

## BauderTEC KSO-P SN

### Roofing membrane



24/06/2025

<b>Product description</b>	Elastomer bitumen self-adhesive capping sheet. The lap of the membrane is equipped with a glass fleece to the underside. This allows the membrane to be sealed with a hot air welder.						
<b>Application fields</b>	Capping sheet in a flat roof system. Used in 'flame-free' areas where a gas torch is prohibited.						
<b>Surface</b>	top:	Charcoal grey mineral					
	bottom:	release film (cold self-adhesive bitumen underside)					
<b>Reinforcement type and weight</b>	polyester fleece 200 g/m <sup>2</sup>						
<b>Article number</b>	1620 0000						

Characteristic	Test method	Unit	Value
<b>Length</b>	EN 1848-1	m	5
<b>Width</b>	EN 1848-1	m	1
<b>Thickness</b>	EN 1849-1	mm	4
<b>Mass per unit area</b>	EN 1849-1	kg/m <sup>2</sup>	5,2
<b>Straightness</b>	EN 1848-1	mm/10m	<20
<b>Reaction to fire</b>	EN 13501-1	-	E
<b>Watertightness</b>	EN 1928	-	passed
<b>Flexibility at low temperature top</b>	EN 1109	°C	≤-30
<b>Flexibility at low temperature bottom</b>	EN 1109	°C	≤-25
<b>Flow resistance at elevated temperature top</b>	EN 1110	°C	≥100
<b>Flow resistance at elevated temperature bottom</b>	EN 1110	°C	≥100
<b>Max. tensile force length</b>	EN 12311-1	N/50mm	≥1000
<b>Max. tensile force transverse</b>	EN 12311-1	N/50mm	≥900
<b>Elongation at max. tensile force length</b>	EN 12311-1	%	≥40
<b>Elongation at max. tensile force transverse</b>	EN 12311-1	%	≥40
<b>External fire performance</b>	CEN/TS 1187	-	Product has been fire tested as part of a system assembly and this information can be obtained in the Fire Test Report available from Bauder Ltd.

#### Product surface finish

The mineral surface finish is a natural rock, also containing slate, basalt, sand and other constituent parts. With



Notified body: GPB, 1724  
EN 13707:2004 + A2:2009

UNITED KINGDOM Bauder Ltd 70 Landseer Road, Ipswich, Suffolk IP3 0DH  
T: +44 (0)1473 257671 - E: [technical@bauder.co.uk](mailto:technical@bauder.co.uk)  
[www.bauder.co.uk](http://www.bauder.co.uk)

Bauder reserves the right to update this data set without prior notice and this document is uncontrolled if printed or stored. Always confirm the latest version is used for the adoption of this product, available from our website: [bauder.co.uk/technical-centre](http://bauder.co.uk/technical-centre). Intended use of this product should be verified with Bauder to ensure suitability and compliance with applicable guidance, regulations, legislations, project requirements, specifications, and installation techniques.

# Technical data sheet

## BauderTEC KSO-P SN

### Roofing membrane



this being a mixture of natural and man-made products, the raw material may differ in colour and shade, over which we have no control. There may also be colour variations between each roll of membrane for which the manufacturer assumes no liability. Over time the colour of the membranes could change due to weather and environmental influences.

#### Product storage guidance

Store the materials outdoors, on end/upright and off the ground with suitable robust UV resistant, flame-retardant tarpaulin. Ensure the product(s) are clear of buildings and any other storage areas. Where there are storage containers on site, these may be suitable for storing products.

#### Pallet size

Pallet size =28 rolls/140m<sup>2</sup> per pallet

#### Storage temperature range

+5°C to +30°C

#### Packaging material

The product will be delivered on wooden pallets with plastic overwrap to protect the product. Each roll has a paper wrapping/tape to the external of the product, which must be removed before use.

#### Handling/PPE

All persons using the product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using/handling the product, installers should be provided with, and wear, suitable personal protective equipment.

#### Shelf life

When stored correctly, the product has a stated shelf life of 9 months. We would suggest additional installation techniques may be required to ensure adequate adhesion is achieved.

#### Disposal guidance

Bitumen waste can be disposed of with household waste or commercial waste similar to household waste (European waste catalogue EWC number 170302 "asphalt tar-free").

#### Re-use options of product

Please refer to EPD stated below in Certification and environmental information.

#### Further information/documents

Current documents such as DoP's (where relevant), brochures, installation guides, etc. can be found by visiting [www.bauder.co.uk](http://www.bauder.co.uk)

#### Certification and environmental information

##### BBA Certificate No.:

10/4744

##### Environmental Product Declaration:

GlobalEPD-IntEPD S-P-00768

##### International Standards Organisation (ISO):

ISO 9001:2015 Quality Management

Certificates EN1271 (UK) and 70499/03-15\_e (Germany)

ISO 14001:2015 Environmental Management

Certificates A10552 (UK) and 70499/03-15\_d (Germany)

ISO 50001: 2011 Energy Management

Certificate 70499/03-15\_c (Germany)

#### Safety Data Sheet

Safety Data Sheets are designed to provide the necessary information to recipients of substances and mixtures in the EU & UK. This product is classed as an article; therefore, this product does not have a requirement for a Safety Data Sheet.



Notified body: GPB, 1724  
EN 13707:2004 + A2:2009

UNITED KINGDOM Bauder Ltd 70 Landseer Road, Ipswich, Suffolk IP3 0DH  
T: +44 (0)1473 257671 - E: [technical@bauder.co.uk](mailto:technical@bauder.co.uk)  
[www.bauder.co.uk](http://www.bauder.co.uk)

Bauder reserves the right to update this data set without prior notice and this document is uncontrolled if printed or stored. Always confirm the latest version is used for the adoption of this product, available from our website: [bauder.co.uk/technical-centre](http://bauder.co.uk/technical-centre).

Intended use of this product should be verified with Bauder to ensure suitability and compliance with applicable guidance, regulations, legislations, project requirements, specifications, and installation techniques.